TRAXON TM/MC 85W-140

000003000862

000000002		
Version 3.0	Revision Date 2016/08/22	Print Date 2016/08/22
SECTION 1. IDENTIFICATION		
Product name :	TRAXON ^{TM/MC} 85W-140	
Product code :	TR8514ICT, TR8514P5R, TR8514P20, TR8514IBC, TR8514DRR, TR8514DRM TR8514, TR8514BLK	
Manufacturer or supplier's details	Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2 Canada	
Emergency telephone num- ber	Suncor Energy: +1 403-296-3000; Canutec Transportation: 1-888- 226-88 996-6666; Poison Control Centre: Consult local tel emergency number(s).	, , , , , , , , , , , , , , , , , , ,
Recommended use of the chem	ical and restrictions on use	
Recommended use :	These products are multipurpose autom lubricants, suitable for use in passenge highway vehicles.	

Prepared by	: Product Safety: +1 905-804-4752
-------------	-----------------------------------

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid
Colour	Dark amber to brown
Odour	No odour or slight petroleum oil like.

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Potential Health Effects

Primary Routes of Entry	: Eye contact Ingestion Inhalation Skin contact
Aggravated Medical Condi-	: None known.

TRAXON TM/MC 85W-140

000003000862

Version 3.0



Print Date 2016/08/22

tion

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 86.86 %

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration
lubricating oils (petroleum), C20-50, hydrotreat- ed neutral oil-based, high viscosity	72623-85-9	1 - 5 %
Polysulfides, di-tert-Bu	68937-96-2	1 - 5 %
Mineral oil		1 - 5 %
Reaction products of bis(4-methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)		1 - 5 %

SECTION 4. FIRST AID MEASURES

If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	 In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	 Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	: Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi-
Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.	Page: 2 / 9 ™ Trademark of Suncor Energy Inc. Used under licence.

TRAXON TM/MC 85W-140

000003000862



Version 3.0	Revision Date 2016/08/22	Print Date 2016/08/22
	cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.	
Most important symptoms and effects, both acute and delayed	: First aider needs to protect himself	i.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local or cumstances and the surrounding environment.	cir-
Unsuitable extinguishing media	: No information available.	
Specific hazards during fire- fighting	: Cool closed containers exposed to fire with water spray.	
Hazardous combustion prod- ucts	: Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), hydrocarbons, smoke and irritating vapours as products of incomplete co bustion.	
Further information	: Prevent fire extinguishing water from contaminating surfact water or the ground water system.)e

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. In case of insufficient ventilation, wear suitable respiratory equipment.
	equipment.

TRAXON TM/MC 85W-140

000003000862



Version 3.0	Revision Date 2016/08/22	Print Date 2016/08/22
Conditions for safe storage	Avoid contact with skin, eyes and clothi Do not ingest. Keep away from heat and sources of ig Keep container closed when not in use Store in original container. Containers which are opened must be kept upright to prevent leakage. Keep in a dry, cool and well-ventilated Keep in properly labelled containers. To maintain product quality, do not stor	nition. carefully resealed and place.
	light.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity	72623-85-9	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

Engineering measures : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Wear face-shield and protective suit for abnormal processing
net: lubricants petro-canada ca/msds		Page: 4

TRAXON TM/MC 85W-140

000003000862



Version 3.0	Revision Date 2016/08/22	Print Date 2016/08/22
	problems.	
Skin and body protection	: Choose body protection in relation tration and amount of dangerous s cific work-place.	
Protective measures	: Wash hands and face before brea handling the product. Wash contaminated clothing befor Ensure that eyewash station and s to the work-station location.	e re-use.
Hygiene measures	: Remove and wash contaminated of ing the inside, before re-use. Wash face, hands and any expose handling.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous liquid
Colour	:	Dark amber to brown
Odour	:	No odour or slight petroleum oil like.
Odour Threshold	:	No data available
рН	:	No data available
Pour point	:	-27 °C (-17 °F)
Boiling point/boiling range	:	No data available
Flash point	:	223 °C (433 °F) Method: Cleveland open cup
Fire Point	:	No data available
Auto-Ignition Temperature	:	No data available
Evaporation rate	:	No data available
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.9054 kg/l (15 °C / 59 °F)

Solubility(ies)

TRAXON TM/MC 85W-140

PETROCANADA

000003000862

Version 3.0	Revision Date 2016/08/22	Print Date 2016/08/22
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Viscosity		
Viscosity, kinematic	: 351.1 cSt (40 °C / 104 °F)	
	26.0 cSt (100 °C / 212 °F)	
Explosive properties	: Do not pressurise, cut, weld, braz pose containers to heat or source	

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- tions	: Hazardous polymerisation does not occur. Stable under normal conditions.	
Conditions to avoid	: No data available	
Incompatible materials	: Reactive with oxidising agents.	
Hazardous decomposition products	: May release COx, SOx, H2S, SiOx, aldehydes, methacry monomers, alkyl mercaptans, sulfides, hydrocarbons, sm and irritating vapours when heated to decomposition.	

SECTION 11. TOXICOLOGICAL INFORMATION


Information on likely routes Eye contact Ingestion Inhalation Skin contact	of	exposure
Acute toxicity		
Product: Acute oral toxicity	:	Remarks: No data available
		Acute toxicity estimate: > 5,000 mg/kg, Method: Calculation method
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available
		Acute toxicity estimate: > 5,000 mg/kg,
		Method: Calculation method

Components:

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

TRAXON TM/MC 85W-140

000003000862



Ecotoxicity	
<u>Product:</u> Toxicity to fish	: Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	: Remarks: No data available
Toxicity to algae	: Remarks: No data available
ternet: lubricants.petro-canada.ca/msds	Page: 7 / 9







000003000862

Version 3.0	Revision Date 2016/08/22	Print Date 2016/08/22
Toxicity to bacteria :	Remarks: No data available	
Persistence and degradability		
Product:		
Biodegradability :	Remarks: No data available	
Bioaccumulative potential		
No data available		
Mobility in soil		
No data available		
Other adverse effects		
No data available		

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

National Regulations

TDG Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

TRAXON TM/MC 85W-140

000003000862

Version 3.0	Revision Date 2016/08/22	Print Date 2016/08/22

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:		
DSL	On the inventory, or in compliance with the inventory	
TSCA	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.	
IECSC EINECS	On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory	

SECTION 16. OTHER INFORMATION

For Copy of SDS	:	Internet: lubricants.petro-canada.ca/msds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-804-4752
Prepared by	:	Product Safety: +1 905-804-4752
Revision Date	:	2016/08/22

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

